

REGO MPT-III Series (80 mm)



Product Description

Feature:

Labels and receipts are available for printing
Industrial standard 1.5 meter Free fall onto concrete
Conform to IP54 resistance to water and dust
Variable interfaces (RS232C, USB, Bluetooth) for option
Support text, barcode and graphic printing
Stand-by and auto turn-off mode for lower power consumption
In field programming – Update Firmware, Download Fonts and Logos
Windows driver for Windows XP/2000/VISTA/7
Demo & SDK for Windows Mobile, WINCE, Symbian, Android

REGO MPT-III Series (80 mm)

Product Specification

Item	MPT-III
Printing Method	Thermal Line
Printing Speed	50~80mm/s
Effective Printing Width	72mm
Resolution	8 dots/mm, 576 dots/line
Print Font	ANK: 8x16, 12 x24 GBK:16x16, 24 x 24
Character per Line	48
Paper Type	Thermal paper/lable paper
Paper Width	80±0.5mm
Paper Roll Diameter	Max: 40.0mm
Roll Core Inner Diameter	13mm(min.)
Paper Thickness	0.06 to 0.07mm
Paper Loading Method	Drop-in easy loading
TPH Reliability	100km
Barcode	1-D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128; 2D:PDF417, QR code, DATA Matrix
Emulation	ESC/POS
Sensor	Paper end sensor, Power near end sensor, Cover open sensor
Interface	RS-232C, USB, IrDA, Bluetooth, WIFI(reserved)
Power Adaptor	DC12V/1A
Battery	DC7.4V,1.5A rechargeable Li-ion battery
Battery Duration	150~200m continuous printing(12.5%density); 1200 receipts(150mm each receipt);80~100m continuous printing(25%density)
Weight	340g
Dimension (WxLxH)	102 x 108 x50mm
Color	Black
Operating Temp	-10~50°C
Storage Temp	-20~70°C
Operating Humidity	20~85%
Storage Humidity	5~95%